Datasheet

COMfortel® 1200

Life can be so easy – Professional ISDN system telephone with illuminated display and function keys





- Large graphic display with automatic background illumination
- Automatic detection of S_0 or U_{P0} connection
- Power-saving mode
- Programmable function keys for engaged, direct dialing and system functions
- Optimal acoustic properties in all operation modes

Your advantages in detail

Looking for a competitively priced phone for your PBX system that offers the same level of comfort as a system phone? Check out the COMfortel 1200 digital system phone: the large illuminated display, handsfree function and direct access to the system's central phonebook show that convenience is the name of the game. Almost every function of your PBX system can be directly controlled via the phone keys – the current status is indicated by an LED in the respective key.

Details such as InterCom with automatic hands-free talking or the central caller list by group prove highly practical for day-today activities. The same applies to the online name search function (backward search) which shows the caller's name on the display and as part of the call data listed in the PBX system.

And since it automatically recognises the connection type, the COMfortel 1200 is ready to operate on any S_0 or U_{P0} port of your ICT system immediately.



COMfortel® 1200

Features at a glance

SYSTEM FUNCTIONS

- 10 programmable function keys
- Automatic background illumination with adjustable brightness and switch-on time
- Ringtone, handset and hands-free speaker volume adjustable
- · Microphone mute
- · Calling number and name display (CLIP/CNIP) if registered in the local and the central phone book of the proprietary ICT system
- Online name search (reverse search), with proprietary ICT systems
- Phone book, 1,600 local entries in the telephone
- Access to the central phonebook of the proprietary ICT
- 100 list entries for callers, outgoing calls and redialling
- Automatic detection of S₀ or U_{P0} connection
- Power supply via the system connection, no external power supply or batteries required
- Power-safe mode
- Telephone lock, emergency calls possible
- Set-up angle adjustable in 3 steps
- Desktop and wall mounting

COMPATIBLE PRODUCTS

- 90118 / COMpact 4000
- 90334 / COMpact 5200
- 90335 / COMpact 5200R
- 90336 / COMpact 5500R
- 90670 / COMmander® 6000

- 90671 / COMmander® 6000R
- 90672 / COMmander® 6000RX
- 90347 / COMfortel® H-200

TECHNICAL SPECIFICATIONS

- Power supply: via internal S₀ or U_{P0} port of the ICT sys-
- Power consumption: 1.1 W min. | 2 W max.
- System connection: S₀/U_{P0} port
- Operating elements: dialing keys with vanity code, 13 function keys, 10 programmable function keys
- Display: graphic display with 128 x 64 pixels, monochrome, with background illumination
- · LEDs: 14, some multi-coloured
- Handset: wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- Hook switch: magnetically switching contact
- · Loudspeaker: 8 Ohm, Ø 52 mm
- Case: plastic
- Colour: black
- Dimensions (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- Weight: approx. 920 g
- · Compliance: CE

DELIVERY

- Basic unit
- Handset with connection cable
- ISDN cable RJ-45/RJ-45 (approx. 3 m long)
- Installation manual and quick start guide

ORDERING INFORMATION Designation: COMfortel® 1200 Article number: 90065 EAN Code: 4019377900659

