

COMfortel® 1400



Feature phone with excellent acoustic properties and a 3.5 inch touch function colour display



- Generous 3.5 inch TFT touch display with resistive touch technology and 65,536 colours
- 13 permanent function keys, 10 programmable function keys
- Separate interface for not cordless headsets
- Automatic detection of S_0 or U_{P0} connection
- Optimal acoustic properties

Your advantages in detail

The COMfortel 1400's 3.5 inch coloured touch display brings a new level of convenience for accessing the most important functions. It can also tell whether the ICT system has an S_0 or U_{P0} port. You can make use of its many talents, such as the integrated 1,600-entry telephone book and the ten programmable keys (on two levels) for line busy, speed dialling and PBX functions, right away. No matter whether you're calling or listening to the optional answering machine (which

works with non-compressed recordings), the acoustic quality is outstanding.

Functions such as live call recording or voice memos prove their usefulness on a daily basis. Use the adjustable supporting feet to get the best angle for reading the display, and upload additional ringtones and personal wallpapers to give the phone that personal touch. A highly visible LED signals incoming calls and messages in the voice mailbox, even if you have mounted the telephone on the wall, directly above the wall socket.

Features at a glance

SYSTEM FUNCTIONS

- 10 programmable function keys, 2 levels
- Programmable function keys (8) as touch function in the display
- Automatic background illumination with adjustable brightness and switch-on time
- Individual background images and ring tones loadable
- Ringtone, handset and hands-free speaker volume adjustable
- Microphone mute
- Calling number and name display (CLIP/CNIP) if registered in the local and the central phone book of the proprietary ICT system
- Online name search (reverse search), with proprietary ICT systems
- Phone book, 1,600 local entries in the telephone
- Access to the central phonebook of the proprietary ICT system
- 100 list entries for callers, outgoing calls and redialling
- Automatic detection of S₀ or U_{P0} connection
- Power supply via the system connection, no external power supply or batteries required
- Power-safe mode
- Telephone lock, emergency calls possible
- Set-up angle adjustable in 3 steps
- Desktop and wall mounting

VOICEMAIL

- Basic activation via the Online Shop and start-up with plugging a Micro SD/SDHC card (not included)
- Announcements (25) and messages (250)
- Call acceptance and announcement dependent on type of call (int./ext./door/group)
- Total capacity depends on the used memory (1 GB represent approx. 30 h recording capacity)
- Voice recording and notepad function
- High-quality audio due to uncompressed recording
- Activation via function keys of the telephone
- Remote activation and message forwarding

COMPATIBLE PRODUCTS

- 90118 / COMpact 4000
- 90334 / COMpact 5200
- 90335 / COMpact 5200R
- 90336 / COMpact 5500R
- 90670 / COMmander® 6000
- 90671 / COMmander® 6000R
- 90672 / COMmander® 6000RX

TECHNICAL SPECIFICATIONS

- Power supply: via internal S₀ or U_{P0} port of the ICT system
- Power consumption: 1.1 W min. | 2 W max.
- System connection: S₀/U_{P0} port
- Headset: separate interface for corded speaker/microphone sets
- Operating elements: dialling keys with vanity code, 13 function keys, 10 programmable function keys (2 levels)
- Memory: Micro SD/SDHC card up to 16 GB, not included
- Display: TFT colour display (3.5" / 8.9 cm, 320 x 240 pixels) with resistive touch and 65,536 colours
- LEDs: 14, some multi-coloured
- Handset: wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- Hook switch: magnetically switching contact
- Loudspeaker: 8 Ohm, Ø 52 mm
- Case: plastic
- Colour: black
- Dimensions (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- Weight: approx. 980 g
- Compliance: CE

DELIVERY

- Basic unit
- Handset with connection cable
- ISDN cable RJ-45/RJ-45 (approx. 3 m long)
- Installation manual and quick start guide

ORDERING INFORMATION

Designation: COMfortel® 1400

Article number: 90069

EAN Code: 4019377900697