Datasheet

COMfortel® M-210



Robust and convenient – this DECT handset is easy to use and has a multitude of practical functions for professional use



- Brilliant voice quality
- · Colour display with easy to use menus
- Robust housing with elegant design
- Features especially for office environments
- Optimum availability of employees due to increased site mobility

Your advantages in detail

The subtle and elegant exterior of our COMfortel M-210 belies the fact that it has a robust core: this DECT handset even withstands being accidentally dropped. At the same time, it provides a long list of practical functions ideally suited for mobile employees in the craft sector, trading and office environments: the brilliant colour display and intuitive menu structure make accessing the local phone book with its 250 name capacity (4 numbers per entry!) easy. If desired, entries can be added to the integrated phone book directly from the call list. And of course

any name search will consider entries in the central telephone system's address list.

Thanks to its Bluetooth® 2.0 interface, you can attach a wireless headset, keeping hands free at all times. The large selection of ringtones lets you distinguish between any number of handsets easily, even if several subscribers get a call simultaneously - an indispensable feature in a professional working environment. The COMfortel M-210 proves its worth by being especially practical, emphasising its readiness for use with up to 24 hours talk time and 130 hours in standby. It is clearly a business handset which considerably improves onsite mobility in an elegant way.



COMfortel® M-210

Features at a glance

PHONE FEATURES

- Backlit colour display (TFT) with 65.536 colours and 128 x 160 pixels
- System date and time in display
- 4-way navigation key
- 2 soft keys
- Bluetooth® 2.0 support for wireless headsets
- Keypad lock, manually or automatically
- 10 ringtones, distinction by internal/external
- Adjustable volume for speaker and ringtones
- Microphone mute
- Signal tones configurable for battery low, out of range and messages
- Global mute (silent mode)
- Signalling in silent mode configurable as display light on, vibration alert or short beep
- Calling list with max. 40 entries for incoming, outgoing and missed calls
- Call back from calling list
- 10 speed dialling numbers
- Vibration call signal
- Call acceptance with any key
- Automatic call acceptance selectable
- Seperate R-key for call-brokering
- Automatic roaming between 15 different DECT installations
- Hands-free mode
- Charging cradle included
- 14 menu languages (en, fr, de, es, it, nl, cz, pl, dk, no, sv, fi, pt, ru)

PHONE BOOK

- Display of calling number (CLIP) and name (CNIP) from local and central phone book in the ICT system (with LDAP capable telephones)
- Name lookup in the central address book of LDAP capable systems and in the local phone book of the handset
- Local telephone book with 250 entries (one number per entry)

Copy from call list into local telephone book

COMPATIBLE PRODUCTS

- 90148 / COMfortel® WS-400 IP
- 90150 / COMfortel® WS-650 IP
- 90145 / COMfortel® WS-Base
- 90152 / COMfortel® WS-R2
- 90146 / COMfortel® WS-R4
- 90118 / COMpact 4000
- 90335 / COMpact 5200R
- 90336 / COMpact 5500R
- 90670 / COMmander® 6000
- 90671 / COMmander® 6000R
- 90672 / COMmander® 6000RX

TECHNICAL SPECIFICATIONS

- Display: colour display (128 x 160 pixels) with 65,536 colours
- Radio interface: DECT/GAP (1.8 GHz / GAP)
- Typical range: 300 m outdoors, 50 m indoors
- Power supply: battery (Li-ion) 3.7 V, 1,150 mAh
- Talk time: up to 24 hours, up tp 16 hours with Bluetooth activated
- Standby time: up to 130 hours, up to 119 hours with Bluetooth activated
- · Case: plastic
- Colour: black, silver
- Dimensions (w x h x d): 48 mm x 146 mm x 19 mm
- Weight handset: approx. 110 g, incl. battery
- Compliance: CE

DELIVERY

- COMfortel Handset
- Charging cradle
- Wall-mounted power supply
- Battery (Li-ion) 3.7 V, 1,150 mAh
- Setup Guide and Quick Guide (German/English)

ORDERING INFORMATION Designation: COMfortel® M-210 Article number: 90160 EAN Code: 4019377901601



Further information can be found at auerswald.de 29.04.2020 - Reserve technical changes Copyright© Auerswald GmbH & Co. KG

