

# U<sub>P0</sub>/S<sub>0</sub> Adapter



## Converts from 2-core U<sub>P0</sub> to 4-core S<sub>0</sub>



- 1 internal S<sub>0</sub> port (PTMP connection, DSS-1) via 2-core connection
- Simple installation using Western plugs, a fixed installation alternatively via screw terminals
- 2 RJ-45 plugs for ISDN system telephones from the COMfortel® series and standard ISDN devices
- LEDs for displaying operational states
- Can be operated as a desktop or wall-mounted device

---

## Your advantages in detail

With the U<sub>P0</sub>/S<sub>0</sub> adapter, ISDN system telephones from the COMfortel series and standard ISDN devices can

be adapted to the U<sub>P0</sub> port of an ICT system. Enables "old" 2-core cables to be useable for ISDN connections.

# Features at a glance

## FUNCTIONS

- Adapter for connection at a 2-wire- $U_{P0}$  port, transforming to 4-wire  $S_0$  interface
- 1 internal  $S_0$  port with 2 plugs for 2 system or ISDN telephones
- Power supply via the  $U_{P0}$  port
- Installation via western plugs, fix installation via screw terminals possible
- LEDs for signalling operating and functional states

## TECHNICAL SPECIFICATIONS

- Operating voltage: via the internal  $U_{P0}$  port of the ICT system

- Connections: 1 x  $U_{P0}$  port for connecting the ICT system, 2 x  $S_0$  port Euro-ISDN (DSS-1), PTMP
- Range of internal  $S_0$  port: approx. 15 m
- Casing material: plastic, grey
- Dimensions (d x h):  $\varnothing$  95 mm x 33 mm
- Weight: approx. 100 g
- Compliance: CE

## DELIVERY

- $U_{P0}/S_0$  Adapter
- $U_{P0}$  connection cable RJ-45/RJ-11 (ca. 4 m)
- Mounting material (screws and dowel)
- User manual

## ORDERING INFORMATION

Designation: UP0/S0 Adapter

Article number: 90436

EAN Code: 4019377904367