

DATASHEET

COMfortel® D-XT20



Maximum variety in business communications

- Intuitive user interface
- Brilliant high-resolution 4.3" display
- 20 self-labelling function keys incl. LED signalling
- USB connection for additional key extensions
- Up to 3 key extensions per telephone
- Supports COMfortel D-200

The new COMfortel D-XT20 simplifies the workflow for frequent call makers: its 20 speed dialling and function keys per extension module provide fast access to keystrokes, user status is visible at a glance via the LED signalling, and its high-resolution 4.3" display and intuitive operator guidance make using all extra functions a breeze. With its modern, functional design, it blends in with any office environment.

Features Overview

System and Comfort Features

- 20 self-labelling and freely programmable function keys with 3 levels as well as polychromatic LED signalling
- Automatic backlight with adjustable brightness and switch-on time
- Telephone tilt angle: 30° or 45°
- Plug-and-Play
- Power supply via the telephone's USB connection¹

Supported IP Telephones

- COMfortel D-200

Technical Data

- Power supply: Via the telephone's USB connection¹ or power supply unit 15VDC, 1.5 A
- USB: USB 2.0 for up to 3 key extensions COMfortel D-XT20
- User elements: 20 freely programmable and self-labelling function keys each with 3 levels, 2 keys for shifting levels quickly
- Display: 4.3" (10.9 cm), 272 x 480 pixels
- Casing: Plastic
- Colour: Black
- Dimensions (WxHxD): 123 mm x 133/100 mm x 145/195 mm
- Weight: 287 g (including device stand)
- Compliance: CE, EN 55032, EN 55024, EN 55035

Scope of Delivery

- COMfortel D-XT20 basic unit
- USB connection cable
- Device stand
- Colour: Black
- Short operation instructions

Ordering Information

- **Designation:** COMfortel D-XT20
- **Item number:** 90264

Accessories

90274 COMfortel D-XT-PS
(wall-plug power supply)

¹ If more than one COMfortel D-XT20 is connected to a telephone, the optional COMfortel XT-PS must be connected to the second COMfortel D-XT20 key extension.

² Depending on the central communication server/cloud PBX